Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: V-TAC

Supplier's address: V-TAC Europe Ltd, bul. Rozhen 41, Sofia, Bulgaria

Model identifier: 212552

Type of light source:

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	+ve and -ve		
(or other electric interface)			
Mains or non-mains:	NMLS	Connected light source (CLS):	No
Colour-tuneable light source:	Yes	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	Only with specific dimmers

Product parameters

Parameter Parameter Value Value General product parameters: Energy consumption in on-8 Energy efficiency G mode (kWh/1000 h), rounded class up to the nearest integer Useful luminous flux (duse), 400 in Correlated colour 1000...10000 indicating if it refers to the flux Sphere (360°) temperature, in a sphere (360°), in a wide rounded to the cone (120º) or in a narrow cone nearest 100 Κ, (90º) or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set On-mode (P_{on}), 8,0 Standby power (P_{sb}), 0,00 power expressed in W expressed in W and rounded to the second decimal Networked standby power (P_{net}) Colour rendering 80 index, rounded to for CLS. expressed in W and rounded to the second decimal the nearest integer, or the range of CRIvalues that can be set Outer Height 4 Spectral power See image dimensions distribution in the in last page 10 Width

Claim of equivalent power(a)-If yes, equivalent power (W)-Chromaticity0,373 coordinates (x and y)0,375Parameters for LED and OLED light sources:R9 colour rendering index value5Survival factor1,00the lumen maintenance factor0,9611	without separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)	Depth	500	range 250 nm to 800 nm, at full-load			
coordinates (x and y)0,375Parameters for LED and OLED light sources:0,375R9 colour rendering index value5Survival factor1,00	Claim of equival	ent power ^(a)	-		-		
Parameters for LED and OLED light sources:R9 colour rendering index value5Survival factor1,00				Chromaticity	0,373		
R9 colour rendering index value5Survival factor1,00				coordinates (x and y)	0,375		
	Parameters for LED and OLED light sources:						
the lumen maintenance factor 0,96	R9 colour rende	ring index value	5	Survival factor	1,00		
· ·	the lumen maintenance factor		0,96				

(a)'-' : not applicable;

(b)'-' : not applicable;

