# **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

### Supplier's name or trade mark: V-TAC

Supplier's address: V-TAC Europe Ltd, bul. Rozhen 41, Sofia, Bulgaria

### Model identifier: 212626

## Type of light source:

| Lighting technology used:     | LED         | Non-directional or directional: | NDLS                       |
|-------------------------------|-------------|---------------------------------|----------------------------|
| Light source cap-type         | +ve and -ve |                                 |                            |
| (or other electric interface) |             |                                 |                            |
| Mains or non-mains:           | NMLS        | Connected light source (CLS):   | No                         |
| Colour-tuneable light source: | No          | Envelope:                       | -                          |
| High luminance light source:  | No          |                                 |                            |
| Anti-glare shield:            | No          | Dimmable:                       | Only with specific dimmers |

**Product parameters** 

#### Parameter Parameter Value Value General product parameters: Energy consumption in on-8 Energy efficiency F mode (kWh/1000 h), rounded class up to the nearest integer Useful luminous flux (duse), 750 in Correlated colour 4 0 0 0 indicating if it refers to the flux Sphere (360°) temperature, in a sphere (360°), in a wide rounded to the cone (120º) or in a narrow cone nearest 100 Κ, (90º) or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set On-mode (P<sub>on</sub>), 8,0 Standby power (P<sub>sb</sub>), 0,00 power expressed in W expressed in W and rounded to the second decimal Networked standby power (P<sub>net</sub>) Colour rendering 80 index, rounded to for CLS. expressed in W and rounded to the second decimal the nearest integer, or the range of CRIvalues that can be set Outer Height 4 Spectral power See image dimensions distribution in the in last page 9 Width

| without<br>separate<br>control gear,<br>lighting<br>control parts<br>and non-<br>lighting<br>control parts,<br>if any<br>(millimetre) | Depth                    | 1 000 | range 250 nm to 800<br>nm, at full-load |       |  |  |
|---|--------------------------|-------|---|-------|--|--|
| Claim of equival  | ent power <sup>(a)</sup> | -     | lf yes, equivalent power (W)            | -     |  |  |
|   |                          |       | Chromaticity                            | 0,378 |  |  |
|   |                          |       | coordinates (x and y)                   | 0,379 |  |  |
| Parameters for LED and OLED light sources:  |                          |       |   |       |  |  |
| R9 colour rende   | ring index value         | 12    | Survival factor                         | 1,00  |  |  |
| the lumen maintenance factor  |                          | 0,96  |   |       |  |  |
| (a)   |                          | ÷     |   |       |  |  |

(a)'-' : not applicable;

(b)'-' : not applicable;

