## **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

LED

Non-directional or

or the range of CRI-

**NDLS** 

**Supplier's name or trade mark:** V-TAC

Supplier's address: V-TAC Europe Ltd, bul. Rozhen 41, Sofia, Bulgaria

Model identifier: 212653

Lighting technology used:

Type of light sou	ırce:	:
-------------------	-------	---

Lighting technology used.	LLD	directional:	NDLS			
Light source cap-type (or other electric interface)	+ve and -ve (because strips are DC voltage and have black and red wires)					
Mains or non-mains:	NMLS	Connected light source (CLS):	No			
Colour-tuneable light source:	No	Envelope:	-			
High luminance light source:	No					
Anti-glare shield:	No	Dimmable:	Only with specific dimmers			
Product parameters						
Parameter	Value	Parameter	Value			
General product parameters:						
Energy consumption in on- mode (kWh/1000 h), rounded up to the nearest integer	10	Energy efficiency class	F			
Useful luminous flux (фuse), indicating if it refers to the flux in a sphere (360°), in a wide cone (120°) or in a narrow cone (90°)	950 in Sphere (360°)	Correlated colour temperature, rounded to the nearest 100 K, or the range of correlated colour temperatures, rounded to the nearest 100 K, that can be set	4 000			
On-mode power (P <sub>on</sub> ), expressed in W	10,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the second decimal	0,00			
Networked standby power (P <sub>net</sub> ) for CLS, expressed in W and rounded to the second decimal	-	Colour rendering index, rounded to the nearest integer,	80			

			values that can be set				
Outer dimensions without separate control gear, lighting control parts and non-lighting control parts, if any (millimetre)	Height	4	Spectral power	See image			
	Width	8	distribution in the range 250 nm to 800 nm, at full-load	in last page			
	Depth	500					
Claim of equivalent power <sup>(a)</sup>		-	If yes, equivalent power (W)	-			
			Chromaticity	0,378			
			coordinates (x and y)	0,379			
Parameters for LED and OLED light sources:							
R9 colour rendering index value		-3	Survival factor	1,00			
the lumen maintenance factor		0,96					

(a)<sub>'-'</sub> : not applicable;

(b)<sub>'-'</sub> : not applicable;

