Product Information Sheet

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

Supplier's name or trade mark: V-TAC

Supplier's address: V-TAC Europe Ltd, bul. Rozhen 41, Sofia, Bulgaria

Model identifier: 2155

_	•			
Typa	Λt	liaht	sourc	Δ.
IVDE	OI.	IIGIIL	3 Uui C	c.

Type of light source:						
Lighting technology used:	LED	Non-directional or directional:	NDLS			
Light source cap-type	+ve and -ve					
(or other electric interface)	(because strips					
	are DC voltage					
	and have black					
Mains or non-mains:	and red wires) NMLS	Connected light	No			
Mains or non-mains:	INIVILS	Connected light source (CLS):	No			
Colour-tuneable light source:	Yes	Envelope:	-			
High luminance light source:	No					
Anti-glare shield:	No	Dimmable:	Only with			
			specific dimmers			
	Product para					
Parameter	Value	Parameter	Value			
General product parameters:						
Energy consumption in on-	7	Energy efficiency	G			
mode (kWh/1000 h), rounded		class				
up to the nearest integer	140 in	Completed	1000 10000			
Useful luminous flux (фuse), indicating if it refers to the flux	140 in Sphere (360°)	Correlated colour temperature,	100010000			
in a sphere (360°), in a wide	Spriere (300)	rounded to the				
cone (120º) or in a narrow cone		nearest 100 K,				
(90º)		or the range of				
		correlated colour				
		temperatures,				
		rounded to the				
		nearest 100 K, that				
On made (5.)	7.0	can be set	0.00			
On-mode power (P _{on}),	7,0	Standby power (P _{sb}), expressed in W	0,00			
expressed in W		expressed in W and rounded to the				
		second decimal				
Networked standby power (P _{net})	-	Colour rendering	60			
for CLS, expressed in W and		index, rounded to				
rounded to the second decimal		the nearest integer,				
		or the range of CRI-				

			values that can be set			
Outer	Height	4	Spectral power	See image		
dimensions	Width	10	distribution in the	in last page		
without separate control gear, lighting control parts and non- lighting control parts, if any (millimetre)	Depth	500	range 250 nm to 800 nm, at full-load			
Claim of equivalent power ^(a)		-	If yes, equivalent power (W)	-		
			Chromaticity	0,182		
			coordinates (x and y)	0,241		
Parameters for LED and OLED light sources:						
R9 colour rendering index value		2	Survival factor	1,00		
the lumen maintenance factor		0,96				

(a)_{'-'}: not applicable;

(b)_{'-'} : not applicable;

