# **Product Information Sheet**

COMMISSION DELEGATED REGULATION (EU) 2019/2015 with regard to energy labelling of light sources

#### Supplier's name or trade mark: V-TAC

Supplier's address: V-TAC Europe Ltd, bul. Rozhen 41, Sofia, Bulgaria

#### Model identifier: 216258

## Type of light source:

Parameter

Lighting technology used:	LED	Non-directional or directional:	NDLS
Light source cap-type	L/N connect		
(or other electric interface)	line ( accessory also have fast connnector)		
Mains or non-mains:	NMLS	Connected light source (CLS):	No
Colour-tuneable light source:	No	Envelope:	-
High luminance light source:	No		
Anti-glare shield:	No	Dimmable:	No

### Product parameters

Parameter

Value

Value

rarameter		value	Tarameter	Value		
General product parameters:						
0,	mption in on- 100 h), rounded st integer	29	Energy efficiency class	E		
dicating if it reformation a sphere (360°)	s flux (фuse), in- ers to the flux in , in a wide cone arrow cone (90º)	3 960 in Sphere (360°)	Correlated colour temperature, rounded to the near- est 100 K, or the range of correlat- ed colour temper- atures, rounded to the nearest 100 K, that can be set	6 500		
On-mode pov pressed in W	ver (P <sub>on</sub> ), ex-	29,0	Standby power (P <sub>sb</sub> ), expressed in W and rounded to the sec- ond decimal	0,00		
(P <sub>net</sub> ) for CLS,	tandby power expressed in W the second dec-	-	Colour rendering in- dex, rounded to the nearest integer, or the range of CRI-val- ues that can be set	80		
Outer dimen-	Height	1 195	Spectral power dis-	See image		
sions without	Width	295	tribution in the	in last page		
separate con-	Depth	13	1			
				- 4/0		

trol gear, light- ing control parts and non- lighting con- trol parts, if any (millime- tre)		range 250 nm to 800 nm, at full-load				
Claim of equivalent power <sup>(a)</sup>	-	If yes, equivalent power (W)	-			
		Chromaticity coordi-	0,313			
		nates (x and y)	0,337			
Parameters for LED and OLED light sources:						
R9 colour rendering index value	9	Survival factor	1,00			
the lumen maintenance factor	0,96					

(a)<sub>'-'</sub> : not applicable;

(b)'\_-' : not applicable;

