


Citana XL 25-CCT-2450LM Triac Dim 244 mm Ø



Technical Details:

Luminous Flux:	2450 lm
LED Output:	25 W
Light Yield:	98 lm/W
Light Temperature:	3000,4000,6000 K
Light Color:	CCT Select
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<6
Beam Angle:	110 °
Light Emission:	downward
Dimmable:	✓
Method of Dimming:	"Triac Phasen-/abschnitt"
LED-Chip:	SMD 2835
Ignition Time:	<0,5 s
Power Consumption:	25 W
Contains Driver:	✓
Power Factor (PF):	>0.9
CC/CV:	CC
Input Lamp:	terminal
Switching Cycles:	>30.000
Electrical Protection Class:	II
Ambient Temperature (TA):	-10°C - 40°C
Storage Temperature:	-10°C - 50°C

Dimensions:	244x85 mm
Cut-Out Dimensions:	195-210 mm
Mounting:	Decke
Montageart:	recessed
IP Class:	20
Housing Color	white
Housing Material:	Thermoplastic
Special Feature of Housing:	IP 44 room side
Cover:	frosted
Net Weight:	483 g
Type of Packaging:	box
Dimensions of Packaging:	245x245x95
Weight incl. Packaging:	0.651 kg
Content Master Package:	20
Dimensions of Master Package:	525x525x510 mm
Weight Master Package:	14,27 kg
Product Line:	ECO Line
Warranty	3 years
Operating Hours:	40.000 h L70/B30
Disposal Obligation:	✓
Customs Tariff Number:	9405499090
Certifications	CE
Barcode:	4250557818429
CCT Select: Farbwahl 3000K, 4000K, 6000K	
inkl. Metallring (chrome dunkel)	
integrierter Treiber Anschlussklemme	
dimmbar mediums Phasen-/ -abschnitt Dimmer	

Information and Downloads:

