

Order number: LG13266

SATURNA HighBay 150-240-840/850-25500-40000LM max.170lm/W DIM 0-10V



Technical Details:

Luminous Flux:	38400 lm
Light Yield:	160 lm/W
Light Temperature:	4000-5000 K
Light Color:	CCT Select
Color Rendering Index:	≥80 Ra
Color Consistency (SDCM):	<4
Beam Angle:	90 °
Unified Glare Rating (UGR):	<25
Light Emission:	downward
Dimmable:	✓
Method of Dimming:	1-10V,PWM
LED-Chip Manufacturer:	Liteon
LED-Chip:	SMD 2835
Number of LED:	624
Ignition Time:	<0,5 s
Input Current:	AC 90-305V, 50/60Hz
Power Consumption:	Power Select (150, 200, 240 W)
Contains Driver:	✓
Driver Manufacturer:	Sosen
Power Factor (PF):	>0.97
Input Driver:	cable with flying leads
CC/CV:	CC
Output Current Adjustable:	✓
Input Lamp:	terminal
Switching Cycles:	>100.000
Electrical Protection Class:	I
Ambient Temperature (TA):	-40°C - 50°C
Storage Temperature:	-40°C - 70°C

Dimensions:	320x120 mm
Mounting:	Decke
Montageart:	surface mounted
IP Class:	65
IK Code:	08
Housing Color	black
Housing Material:	aluminum
Coating:	lacquered
Cover:	Lens
Net Weight:	2600 g
Type of Packaging:	box
Weight incl. Packaging:	4.1 kg
Content Master Package:	1
Dimensions of Master Package:	375x375x200 mm
Product Line:	Advance Line
Warranty	5 years
Operating Hours:	100.000 h L70/B50
Disposal Obligation:	✓
Customs Tariff Number:	9405119090
Certifications	CE,LM80,D
Barcode:	4250557823980
150W: 25500lm, 200W: 33000lm, 240W: 38400lm	
TGIC Beschichtung/Coating	
UGR <19 mit 60° Linse, max. 170lm/W	
1-10V Dim und 12V DC Ausgang für Sensor	
vorbereitet für Radar Sensor	

